





(\_\_\_\_\_) 1P65

RDM

# **POSEIDON WASH XS** Powerful & versatile Outdoor Led Wash

- OUTDOOR LIGHTING ESSENTIAL
- TOURING-READY, COMPACT HOUSING
- 7 RGBL HIGH POWER LEDS
- 4° 58,8° ZOOM ANGLE
- IP65 RATING

The Poseidon Wash XS is a small, powerful and versatile IP65 rated wash fixture, offering smooth projections, intense beams and a very silent operation. Powered by 7, individually controllable, RGBL LEDs, the fixture comes with a wide zoom, ranging from 4° to 30° (36° in wide mode). Protected against moisture and dirt. The Poseidon Wash XS is a must-have fixture with a good value for money for any indoor or outdoor application. IP65 rating, together with the specially designed lens and fast zoom, offers outstanding wash characteristics. All LEDs can be controlled manually, but the on-board macro engine can also be used to create complex effects easily. The strong aluminum housing ensures the product is 'Rock and Roll' proof.





## POWER

INPUT VOLTAGE STANDBY POWER TOTAL POWER CONSUMPTION TYPICAL CURRENT POWER PLUG TYPE 100 - 240 VAC, 50/60HZ 28W 357W 1,6A SEETRONIC POWERCON TRUE 1

#### SOURCE

LED COLOR DIMMING FREQUENCY 7X RGBL 1200 - 10.000HZ

10011 LUX

425.8 LUX

250273 LM

# OPTICAL

NORMAL MODE BEAM ANGLE:

WIDE MODE BEAM ANGLE:

4° ~ 29,8° (BEAM ANGLE 50%) 4° ~ 37,6° (FIELD ANGLE 10%) 4° ~ 39.6° (BEAM ANGLE 50%)

4° ~ 58.8° (FIELD ANGLE 10%)

## PHOTOMETRIC

OUTPUT @4°/5M OUTPUT @30°/5M LUMINOUS FLUX @4°

#### EFFECTS

COLOR MIXING EFFECTS ZOOM DIMMER SHUTTER PAN TILT CCT

### HARDWARE

INTERFACE SOFTWARE UPLOAD RGBL, VIRTUAL COLOUR WHEEL (LEE) INTELLIGENT MACRO ENGINE 36° IN WIDE MODE 5 DIM MODE, 8 OR 16 BIT 1 - 20 HZ 540° (16BIT) 270° (16BIT) CCT CONTROL +/- GREEN CORRECTION, TUNGSTEN EMULATION

OLED DISPLAY WITH AUTOMATICAL ROTATION VIA DMX (EXTERNAL BOX)





HEAT MANAGEMENT	
COOLING TYPE	ADVANCED, SILENT HEATPIPE COOLING
Max. Ambient temp.	TA MAX=40°C
MIN. AMBIENT TEMP.	TA MIN=-20°C
CONTROL	
CONTROL PROTOCOL	USITT DMX512
DMX CHANNELS	20/27/55 CH
RDM	YES
	YES
DMX INPUT CONNECTION	5-PIN
INSTALLATION	
IP RATING	IP65
ORIFNTATION	ANY
ORIENTATION	AINT
HOUSING	
SAFETY ATTACHMENT POINT	YES
	TLO
PHYSICAL	
NET PRODUCT WEIGHT	12.7KG
LENGTH	202MM
WIDTH	300MM
HEIGHT	467MM
ACCESSORIES	
INCLUDED ITEMS	MANUAL, POWER CABLE
	n de la Verse de la
APPROVALS	
APPROVED CERTIFICATIONS	CE, ROHS
INFORMATION	
ARTICLE NUMBER	160037
EAN CODE	8719189163278
	Weind and the second